



Datasheet

# Sadolin Classic

**Description:** Thin varnish based on synthetic resin in organic solvent, with added UV and weather resistant pigments.

**Properties:** Recommended for the protection of exterior wooden surfaces: building elements, structures, facades, fences, garden furniture, ornaments. It forms a protective layer that gives durability to wood and effectively protects against UV radiation, weathering and wood pests. It is prohibited to apply to wooden surfaces that come into direct contact with food, feed or drinking water.

**Appearance:** Translucent

**Colour:** colourless – light oak – mais – palisander – pine – redwood – teak – walnut

**Colouring:** The available colours can be mixed with each other in any ratio (the colourless version must not be more than 30% in the final mixture).

**Application:** Apply to clean, perfectly dry and sound wood (humidity below 18%). Any resin or grease stains on the wood surface are removed with synthetic thinner. The ambient temperature should be between 5°C - 30°C. Do not apply in conditions of high humidity (over 65%). Avoid application under direct sunlight. The product should be thoroughly homogenised before and during use. Apply only with a brush in the direction of the wood fibres.

**Recommended coating system:** apply 2 - 3 coats of Sadolin Classic

**Reconditioning:** Previously painted or varnished surfaces are stripped and sanded to clean, sound wood and then proceed as above.

**Drying:** at 20°C: to touch - 2 hours, in depth - 24 hours; between layers - 24 hours

**Coverage:** 10 - 14 m<sup>2</sup> / litre for finished wood, 7 - 12 m<sup>2</sup> / litre for unfinished wood; figures are indicative and may depend on wood species, surface quality or atmospheric conditions at the time of application.

**Tool maintenance:** Immediately after use wash with synthetic thinner. Remove as much product as possible from the tools before washing.

**Storage:** 60 months from the date of manufacture, in the original, hermetically sealed packaging, at temperatures between 5°C - 30°C, away from radiant heat sources.

Use the product in well-ventilated areas. Do not eat or smoke while using the product. Avoid contact with skin and eyes. Do not pour the rest of the product down the drain. The use of empty packaging for food storage is prohibited.



Export dept – Leuvensesteenweg 248B – 1800 Vilvoorde

This fact sheet has been compiled on the basis of information available at this time. Read the instructions for use carefully and do not use the product for any purpose other than that described above. For information on health and environmental protection, ask your distributor for the safety data sheet.

15.10.2019