



## BONDEX Exotic Oil

<b>Product Code</b>	440090
<b>Product Name</b>	BONDEX Exotic Oil
<b>Recommended for</b>	Garden Furniture
<b>Available sizes</b>	0.75 L - 2.50 L

## 1 Product Description

1.1	Product Type:	Natural teak oil. Resistant to water and alcohol. Based on special oils.
1.2	Manufacturer:	Dyrup A/S - Gladsaxevej 300 - 2860 Søborg - Denmark - Phone: +45 39 57 93 00 - www.dyrup.com
1.3	Where to use:	Garden furniture made of wood - in particular exotic and tropical woods, as well as noble indoor woods.
1.4	Special Qualities:	For interior/external use. Enhances the wood grain. High penetration. Provides weather proof protection. Enables wood to recover its natural balance. Easy maintenance.
1.5	Colour Range:	• 900 Clear • 729 Teak
1.6	Form Supplied:	Ready to use.

## 2 Composition

2.1	Binder:	Alkyd.
2.2	Solvents:	White spirit.
2.3	VOC-content:	Out of scope.
2.4	Pigments:	n/a

## 3 Technical Data

3.1	Specific gravity:	App. 0.8 kg/l.
3.2	Viscosity:	n/a



---

## 3 Technical Data

---

3.3	Flash point:	62°C, Pensky Martens.
3.4	Gloss:	Matt.
3.5	Solid content:	App. 50 W/W% / 44,5 v/v%.
3.6	Odour:	Strong.
3.7	Coverage	7-12 m <sup>2</sup> /l, depending on the type of wood and the state of substrate.
3.8	Drying time:	<u>Touch dry</u> : app. 6-12 hours. <u>Recoatable</u> : App. 24 hours. Measured at 23°C and standard humidity of 60%.
3.9	Weather resistance:	Water repellent.
3.10	Thinning:	Do not thin.
3.11	Storage:	Store frost free.
3.12	Shelf life:	5 years in unopened container.

---

## 4 Surface and preparation

---

4.1	In general:	Stir well before and during application. Keep container firmly closed after use.
4.2	Substrate:	The surface must be clean, dry and solid.
4.3	Humidity / Moisture content:	The wood moisture at the time of the treatment must not exceed 18%.

---

## 5 Treatment

---

5.1	Application method:	Soft cloth or brush. Do not apply at temperatures below 5°C and/or above 80% relative humidity.
5.2	Pre-treatment:	Clean surface with white spirit. Remove stains using sandpaper soaked in BONDDEX Exotic Oil.



- 5.3 Treatment: Apply using a soft cloth or paintbrush. Wipe off surplus with a clean cloth.
- 5.4 Renovation of previously treated wood: Maintenance: App. Once a year with 1-2 applications of BONDEX Exotic Oil.
- 5.5 Cleaning of tools Clean tools immediately with white spirit.

---

## 6 Safety precautions

---

- 6.1 In general Common safety rules for work with paints and varnishes must be observed. Further information is available from our Material Safety Data Sheet.
- 6.2 Safety instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains 2-butanone oxime. May produce an allergic reaction.

---

## 7 Disposal

---

- 7.1 Disposal: Do not empty into drains or into the environment. Product waste must not be poured into the sewers, water reserves or soil. Left over product should be handed in at your local waste disposal. Empty can may be recycled (check with your local waste disposal site or your local authorities).

---

The purpose of this Technical Data Sheet is to provide our clients with information about the properties and characteristics of the product. The information provided is based on tests conducted by us under usage conditions that comply with the prevailing standards. Our recommendations for use are for information only, and in no event shall they take precedence over any specific recommendation taking into account the nature and conditions of a particular site, nor shall they engage PPG's liability. before all applications of the product, clients should check that this document has not been ammended by a more recent version, which takes into account new technical data. This version annuls and replaces all previous versions of Technical Data Sheets relating to this product.

---